



TLS 16
16L chilled water/hr

The TLS is a compact external chiller that can dispense 16L chilled water per hour. With provision for adequate ventilation, it can be conveniently located in a cupboard or out-of-the-way place.

The TLS has rounded edges that maximise air flow to avoid overheating of the unit. It can be connected to the mains or a low pressure filtration system and its 3L holding tank is easily backwashed to remove any sediment buildup.

The TLS operates on the economical 'chill on demand' or 'instantaneous' principle; water is chilled as it flows through the unit. The unit turns on in response to a drop in pressure (ie. when a tap is used), and switches to 'sleep' mode when there is no demand.

The TLS can be connected to the mains or a low pressure filtration system. It comes with 2 year warranty, along with Watermark certification.

SPECIFICATIONS

Dimensions L x W x H (cm):	48.5 x 29 x 32
Weight (kg):	21
Storage Tank Vol (L):	3
Water Fittings:	1/4" BSP inlet/outlet
Chilled water (L/hr):	16

Length

Width

Height

TLS chillers are
manufactured by Frigmac and
carry a **2 Year Warranty**



Functional

Working Principle:	Vapour Compression
Refrigerant:	R134a
Temperature Control:	Chill on demand
Output L/hr:	16
Refrigerant:	R134a
Max Working Pressure:	350kpa (limiting valve supplied)
Power supply:	220/240 volts/ 50Hz/1PH/1.92 amps/400 watts/IP21
Power Plug:	Standard Australian 10 amp

Materials & Finishing

Side Panelling:	Stainless Steel
Nuts/bolts/screws:	Stainless Steel
Colour:	White/silver